

# Mini Flood Light

15W | 4000K | 120-277V | Knuckle Mount

Ideal for landscaping, patio, and security lighting, signs, and building facades  
Excellent replacement for quartz halogen fixtures



Suggested Substitutions:  
FLM-15W-40K-LV-YK



## TECHNICAL DATA




### LIGHT SPECIFICATIONS

Lumens	1,603 lm
Efficacy	111.05 lm/W
CCT	4000K
CRI	80
Dimmable	No
L70 Life	50,000 hrs
Warranty	10-year


### APPROVALS AND LISTINGS

cUL	E482965
-----	---------

### DIMENSIONS



### ISOCANDELA



### ELECTRICAL

Wattage	15W
Voltage	120-277V
Power Factor	0.9
THD	18.39%
Operating Temp	-40 to 50°C

### CONSTRUCTION

Housing	Aluminum Alloy
Finish	Bronze
IP Rating	IP65
Carton Weight	10.4 kg
Carton Qty	8
Carton Dimensions	484 x 302 x 297 mm

### SUGGESTED SUBSTITUTION

FLM-15W-40K-LV-YK

### ILLUMINANCE AT A DISTANCE

Distance (ft)	Illuminance at a Distance		
	Center Beam fc	Beam Width	
17.0ft	2.07 fc	50.5 ft	45.1 ft
34.0ft	0.52 fc	101.1 ft	90.2 ft
51.0ft	0.23 fc	151.6 ft	135.3 ft
68.0ft	0.13 fc	202.2 ft	180.4 ft
85.0ft	0.08 fc	252.7 ft	225.6 ft
102.0ft	0.06 fc	303.3 ft	270.7 ft

■ Vert. Spread: 112.1°  
■ Horiz. Spread: 106.0°

Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | [ordersbc@csc-led.com](mailto:ordersbc@csc-led.com)