

# LHB03 Linear High Bay

110W | 5000K | 120-347V



Ideal for warehouses, factories, workshops, and more  
Energy efficient replacement for traditional fluorescent fixtures and HID high bays



120-347V Driver  
with 4kV surge protection

0-10V Dimmable

Instant Start  
with no flickering  
or humming

Newly Designed,  
Shatterproof  
Polycarbonate Optics  
meet/exceed DLC 5.1  
glare standards

Centre Knockout Allows  
for Easy Installation of an  
Optional Motion Sensor  
(sold separately)

Complete with  
10' Cord Whip



Mounting Hooks Included  
2 x mounting hooks and 2 x 40" chains


Accessories (Sold Separately):  
Motion Sensor (HB01DMS-A), Motion Sensor Remote (HB01R),  
Wireguard (LHB-110-165-WG), Bracket (LHB-BRACKET-SM)



HB01DMS-A



HB01R



LHB-110-165-WG



LHB-BRACKET-SM

## TECHNICAL DATA




### LIGHT SPECIFICATIONS

Lumens	14,717 lm
Efficacy	138.16 lm/W
CCT	5000K
CRI	82
Dimmable	0-10V
Beam Angle	90°
L70 Life	>51,000 hrs
Warranty	5-year


### APPROVALS AND LISTINGS

cUL	E482965
DLC Premium	PLCEZHTN7AZQ

### ILLUMINANCE AT A DISTANCE



### ISOCANDELA



### ELECTRICAL

Wattage	110W
Voltage	120-347V
Surge Protection	4kV
Auxiliary Output	12V
Power Factor	0.9
THD	15%
Operating Temp	-25 to 50°C

### CONSTRUCTION

Housing	Steel
Finish	Powder Coat
Finish Colour	White
IP Rating	IP20
Net Weight	6.2 kg
Gross Weight	7.8 kg
Product Dimensions	630 x 300 x 48 mm
Carton Qty	2
Carton Dimensions	720 x 360 x 185 mm

### ACCESSORIES (SOLD SEPARATELY)

HB01DMS-A	Motion Sensor
HB01R	Remote for Motion Sensor
LHB-110-165-WG	Wireguard
LHB-BRACKET-SM	Pendant Mounting Bracket

NOTE: Remote (HB01R) is **required** for motion sensor (HB01DMS-A) to function.

### DIMENSIONS

