

# 40W Tri-proof (4')

Water-proof, dust-proof, damp-proof, and vapour-proof  
IP66 - Ideal for workshops and work cells

Can be surface mounted or suspended

Power out  
(Can be daisy chained)

High impact frosted cover  
delivers low glare

Removable end caps  
with silica gel gasket

Power in

Continuous aluminum extruded base  
for rigidity and heat dissipation

Power cord and/or power connectors need to be ordered separately as required.  
Please contact CSC LED or your Sales Rep for custom cord requirements.

## TECHNICAL DATA



### LIGHT SPECIFICATIONS

Lumens	5,200 lm
Efficacy	130 lm/W
CCT	5000K
CRI	80
L70 Life	50,000
Dimmable	No
Warranty	5-year

### ACCESSORIES



Double ended Cord  
SL-1MCORD-DOUBLE



Connectors  
SL-3PIN-MALE



Shown with double ended cord for daisy chaining (sold separately), and connectors (sold separately, cable not included)


### ELECTRICAL

Wattage	40W
Voltage	100-277V
Power factor	0.90
THD	10%
Operating temp	-40 to 40°C

### CONSTRUCTION



Housing	Aluminum / Polycarbonate
IP rating	IP66
Carton qty	6

### DIMENSIONS



1200 x 94 x 69 mm

### INSTALLATION INSTRUCTIONS



Shown with mounting clips (included)