



Temporary Work Light String Instructions

Caution:

1. Do not operate with generator circuits.
2. Abide by local bylaws.
3. Please turn off the power before installation or maintenance.
4. Proper grounding is required to ensure safety.

Notice:

1. To avoid possibility of electrical shock or fire, installation personnel must have electrical knowledge.
2. Please wear gloves to avoid injury before installation.
3. Disconnect power in the event of smoke or fire.

Attention:

1. Please check for shipping damage prior to installation and notify distributor if noted.
2. Please read the installation instruction carefully to check whether all the accessories are complete. After confirmation, install the fixture according to installation steps.

Warning / Avertissement

Suitable for Wet Location Use. CAUTION: RISK OF ELECTRIC SHOCK, Do not use with extension cord near water or where water may accumulate. Keep lamp at least 16 feet from pools and spas. Keep plugs and receptacles dry. For use only on GFCI protected circuits.

SUITABLE FOR OPERATION IN AMBIENT NOT EXCEEDING 45°C

Only connect to adjacent units

CAUTION – Risk of Electrical Shock or Fire, Wire can't used over maximum Amp circuit, Refer to the table below.

14AWG Max. 12A	16AWG Max. 10A	18AWG Max. 8A
----------------	----------------	---------------

CONVIENT AUX EMBLEMENTS MOUILLÉS ATTENTION: RISQUE D'ELECTROCUTION, ne pas utiliser de rallonge près d'une source d'eau ou de tout endroit où de l'eau pourrait s'accumuler. Gardez la lampe au moins 16 pieds de piscines et spas. Laissez les prises de courant sèches.

Utiliser uniquement sur des circuits protégés GFCI.

PEUT ÊTRE UTILISÉ À UNE TEMPÉRATURE AMBIANTE N'EXCÉDANT PAS 45°C

Se connecter uniquement aux unités adjacentes

ATTENTION – RISQUE DE CHOC
ATTENTION – RISQUE D'INCENDIE

2 Installation Methods: A and B

(Please choose the most suitable installation method for the purchased product as per your needs.)

A Installation steps

1. Turn off the power before installation, check and make sure the waterproof connector is well connected and the cap is tightly closed (Figure 1);
2. Hook the ring and fix the hook to the wall or object (Note: make sure the wall or object is strong enough) (Figure 2);
3. Connect the plug and socket and turn on the power.




Figure 1




Figure 2

B Installation steps

1. Open the protective cover of the waterproof connector at the end of the fixture (Figure 3), and loosen the tightening nut of the fixture (Figure 4);
2. Connect the fixtures together (Figure 5), and repeat to connect more fixtures. See the maximum quantity of connections for each fixture below.

Wattage	Cord sets	Max.linkable
5W	14AWG	288PCS
	16AWG	240PCS
	18AWG	192PCS
10W	14AWG	144PCS
	16AWG	120PCS
	18AWG	96PCS

Wattage	Cord sets	Max.linkable
15W	14AWG	96PCS
	16AWG	80PCS
	18AWG	64PCS
20W	14AWG	72PCS
	16AWG	60PCS
	18AWG	48PCS

3. Hook the ring and fix the hook to the wall or object (Note: make sure the wall or object is strong enough) (Figure 3);
4. Connect the plug and socket and turn on the power.




Figure 3




Figure 4




Figure 5