

100W




AREA / FLOOD LIGHT, HV



Ideal for outdoor applications such as parking lots, construction sites, storage and rail yards, industrial locations, marinas, billboard/sign illumination, and more

122+ LM/W



Quick Change Mounting Options (additional cost):
Slip Fitter, Round Pole Arm, or Square Pole Arm

TECHNICAL DATA




LIGHT SPECIFICATIONS

| | |
|--------------|--------------------------------|
| Lumens | 12,674 lm |
| Efficacy | 122.81 lm/W |
| CCT | 5000K |
| Distribution | Type III, Type II + V optional |
| CRI | 80 |
| Dimmable | 0-10V |
| Warranty | 10-year |


APPROVALS AND LISTINGS

| | |
|-------------|--------------|
| cUL | E352127 |
| DLC PREMIUM | PLFX2AIMGGTU |

DIMENSIONS



ISOCANDELA PLOT



ILLUMINANCE AT A DISTANCE

| | Center Beam fc | Beam Width |
|---------|----------------|-------------------|
| 17.00M | 0.99 fc | 41.69 M 101.45 M |
| 34.00M | 0.25 fc | 83.38 M 202.92 M |
| 51.00M | 0.11 fc | 125.07 M 304.37 M |
| 68.00M | 0.06 fc | 166.76 M 405.84 M |
| 85.00M | 0.04 fc | 208.45 M 507.30 M |
| 102.00M | 0.03 fc | 250.14 M 608.77 M |

■ Vert. Spread: 101.6°
 ■ Horiz. Spread: 142.9°

ELECTRICAL

| | |
|----------------|--------------|
| Wattage | 100W |
| Voltage | 277-480V |
| Power factor | 0.90 |
| THD | 15% |
| Operating temp | -40 to 40° C |

CONSTRUCTION

| | |
|------------|-------------------|
| Housing | Die cast aluminum |
| Finish | Anodized finish |
| Colour | Bronze |
| IP rating | IP65 |
| Weight | 10.47 lbs |
| Carton qty | 1 |

MOUNTING OPTIONS



Complete with Standard Trunnion Mount
Product #: FL03-100W-50K-HV



Optional Adjustable Slip Fit Mount
Product #: FL03-TA
(Available at an additional cost)



Optional Round Pole Arm Mount
Product #: FL03-TB
(Available at an additional cost)



Optional Square Pole Arm Mount
Product #: FL03-TC
(Available at an additional cost)



Photocell sensor available
Product #: FL03-PC-HV
(Available at an additional cost)