

DLC OP/

HBE 100W High Bay

Smart and stylish design for better cooling and high lumen efficacy Optional motion sensor and/or yoke available





Impact resistant, high grade polycarbonate lens will not yellow

Suitable for use in hockey rinks and food processing facilities





Shown with OPTIONAL MOTION SENSOR KIT #HBE-F-MS-IO



www.csc-led.com

TECHNICAL DATA



LIGHT SPECIFICATIONS

Lumens	13,092
Efficacy	131.53 lm/W
CCT	5000K
Beam angle	90°
CRI	82.8
Rated hours	50,000
Warranty	5-year

APPROVALS AND LISTINGS

cUL	E482965
DLC	PBWSR2WE

ILLUMINANCE AT A DISTANCE

Illuminance at a Distance				
Center Beam fc		Beam Width		
17.0ft	21.0 fc	35.3 ft	35.2 ft	
34.0ft	5.3 fc	70.5 ft	70.4 ft	
51.0ft	2.3 fc	105.8 ft	105.6 ft	
68.08	1.3 fc	141.0 ft	140.8 ft	
85.0ft	0.8 fc	176.3 ft	176.1 ft	
102.0R	0.6 fc	211.5 ft	211.3 ft	
Vert. Spread: 92.1°				
Horiz. Spread: 92.0°				

ELECTRICAL

Wattage	100W
Voltage	120-277V
Power factor	0.97
THD	9.78%
Operating temp	-40 to 40°C


CONSTRUCTION

Housing	Aluminum
Finish	Powder-coat
Colour	Black
IP rating	IP65
Weight	12.78 lbs
Carton qty	1

DIMENSIONS

Φ14"*5.2"

ISO CANDELA PLOT



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com



8-540 Jamieson Parkway, Cambridge, ON N3C 0G5 P: 519.880.9833 888.900.9885 E: info@csc-led.com orders@csc-led.com